

## IMPACT WRENCH 1/2"

**Model** Part#  
**RC2257** 8951000037

Model	RC2257
Anvil	1/2"
Working Torque	680 Nm
Max Torque	950 Nm
Speed	8950 min <sup>-1</sup>
Weight	2.5 kg
Hose	8 mm
Dimension axbxc	213x194x70 mm
Air cons.	200 l/min
Air cons.	610 l/min
Air inlet	1/4" IG
Impact system	DUOPACT
Sound LpA	94 dB(A)
Vibration	6.8 m/s <sup>2</sup>

950 Nm max. Only 2,5 kg DUOPACT-SYSTEM



- 1/2" square drive impact wrench
- One hand operation
- 3+3 position regulator and F/R shift
- 950 Nm max, power in reverse
- A silencing exhaust hose can be attached
- Long handle

**Model** Part#  
**RC2257K** 8951000089

- Content set:
- RC2257
- 10-11-12-13-14-15-16-17
- 18-19-21-22-26-27
- DUS36
- Oil bottle



Anti scratch protected

**Model** Part#  
**RS414WP** 8951012363



- 85 mm long 1/2" socket
- SW17 / 19 / 21 / 22 mm
- extra thin-walled for alloy rims
- impact proof chrome-molybdenum quality
- individual sockets also available

**Model** Part#  
**RC2263TL** 8951077007



Model	RC2263TL
Anvil	1/2"
Working Torque	680 Nm
Max Torque	900 Nm
Speed	7800 min <sup>-1</sup>
Weight	1,9 kg
Hose	8 mm
Dimension axbxc	190x185x70 mm
Air cons.	170 l/min
Air cons.	515 l/min
Air inlet	1/4" IG
Impact system	TORQUE LIMITED
Sound LpA	93.3 dB(A)
Vibration	13.96m/s <sup>2</sup>


900 Nm max.



- 1/2" TL wrench/ impact wrench
- Special torque limited mechanism does not deliver more than 90 Nm in forward
- Full power in reverse - 900 Nm max
- Lightweight composite motor housing
- Robust F/R shift with 1 position regulator in forward
- A silencing exhaust hose can be attached
- Rubber protector on front housing

Anti scratch protected

**Model** Part#  
**RS413LWP** 8955000054



- 130 mm long 1/2" socket
- SW17 / 19 / 21 mm
- extra thin-walled for alloy rims
- impact proof chrome-molybdenum quality
- individual sockets also available

**Model** Part#  
**RC2277** 8951000025

Model	RC2277
Anvil	1/2"
Working Torque	900 Nm
Max Torque	1250 Nm
Speed	8200 min <sup>-1</sup>
Weight	2 kg
Hose	8 mm
Dimension axbxc	194x188x70 mm
Air cons.	245 l/min
Air cons.	760 l/min
Air inlet	1/4" IG
Impact system	DUOPACT
Sound LpA	93 dB(A)
Vibration	9.7 m/s <sup>2</sup>

1250 Nm max.



RODCRAFT  
Premium



- 1/2" square drive impact wrench
- 1250 Nm maximum real torque in reverse
- The Beast Aluminum alloy clutch housing
- Twin hammer mechanism
- Friction ring socket retainer
- Full teasing trigger
- Curved handle with Thermo-Plastic Rubber injected in housing for a durable and comfortable grip, Resistant to most chemicals used in workshops
- NEW power setting system : 1 hand-operation, 1 position in reverse & 3 positions in forward
- 360° swivel air inlet

**Model** Part#  
**RC2277K** 8951000182

- RC2277
- Long Protected sockets:  
17 - 19 & 21 mm

