

Ram | RA 4321 C

Specifications		
article number		150.032.045
model		RA 4321 C
short description		Ram
equipped with (connector type)		CORE
max. working pressure	bar/Mpa	720 / 72
spreading / pulling stroke	mm	250
retracted length	mm	512
extended length	mm	762
max. spreading force	kN/t	161 / 16.4
pulling force over full stroke	kN/t	50 / 5.1
required oil content (effective)	CC	389
number of plungers		1
weight, ready for use	kg	11.1
temperature range	°C	-20 + 55
dimensions (LxWxH)	mm	512 x 122 x 338

Safety factors / tests		
endurance test tool	1000 cycles of spreading and pulling while the tool is loaded	
endurance test dead man's handle	6000 cycles	


Norms	Tested	Classification
EN 13204	\checkmark	R161/250-11.1
NFPA 1936	\checkmark	

Standard supplied with

Built-in Speed Valve

Accessories	
Extension Pipe 500 mm	150.006.204
Extension Pipe 330 mm	150.006.372
Extension Pipe 165 mm	150.006.373
Ram Heads 16 Ton	150.014.062
Accessory Kit AS 4300 A	150.182.269
Connection Piece	150.182.295
Accessory Kit AS 4300 B	150.182.296
Pulling Chains, Set	150.582.152
Ram Support HRS 22	150.181.011
Ram Support HRS 22 NCT	150.003.105
Rim Adapter, Set	150.182.580
Wedge Piece	150.181.324
Conical Tip	150.181.325
Pulling Attachments Set	150.582.281
Pulling Chains, Set in Case	150.582.021
Base Plate, Round	150.181.326







Holmatro | www.holmatro.com

© Holmatro 2015-10-28

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro N.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.