


APPARATUS TYPE			Exchange surface (m ²)	CAPACITY (l)		INDUSTRIAL VERSION		B	C	MAXIMUM ADMISSIBLE TEMPERATURE (°C)		
"Narrow" baffles spacing	"Medium" baffles spacing	"Wide" baffles spacing		SHELL side	TUBES side	A	Empty weight (kg)			With " nitrile " gaskets		
AF07SFQ7AA	AF07MFQ7AA		0.57	1.6	1.7	363.7	12.0	160	114	100		
AF08SFQ7AA		AF08LFQ7AA	0.69	2.0	1.9	417.7	12.6	214	168	150		
AF09SFQ7AA	AF09MFQ7AA	AF09LFQ7AA	0.84	2.4	2.1	482.7	13.5	279	233	MAXIMUM ADMISSIBLE PRESSURE (bar)		
AF10SFQ7AA	AF10MFQ7AA	AF10LFQ7AA	1.02	2.9	2.4	559.7	14.6	356	310	Working	Testing	
AF11SFQ7AA	AF11MFQ7AA	AF11LFQ7AA	1.24	3.5	2.7	652.7	15.8	449	403			
AF12SFQ7AA	AF12MFQ7AA	AF12LFQ7AA	1.50	4.2	3.1	764.7	17.4	561	515	SHELL side	16	24
AF13SFQ7AA	AF13MFQ7AA	AF13LFQ7AA	1.81	5.1	3.6	898.7	19.1	695	649			
AF14SFQ7AA	AF14MFQ7AA	AF14LFQ7AA	2.18	6.2	4.2	1059.7	21.3	856	810	TUBES side	10	15
AF15SFQ7AA	AF15MFQ7AA	AF15LFQ7AA	2.62	7.4	4.9	1251.7	23.8	1048	1002			
AF16SFQ7AA	AF16MFQ7AA	AF16LFQ7AA	3.16	8.9	5.7	1483.7	26.9	1280	1234			
AF17SFQ7AA	AF17MFQ7AA	AF17LFQ7AA	3.80	10.8	6.7	1761.7	30.6	1558	1512			



11 rue Pasteur - BP 8
F-78601 MAISONS-LAFFITTE CEDEX
Tél.: +33 (0) 1 39 62 06 56 - Fax: +33 (0) 9 82 63 67 02
info@picker.fr - www.picker.fr

Manufacturing according to PICKER standard

External painting = Primer paint colour grey RAL 7046

HEAT EXCHANGERS

AF (07 to 17) .FQ7AA

Industrial version with fluid "four passages" on TUBES side

FORMAT A4	CODE N° G. POHU / P5000GB.DWG	PRODUCT DATA SHEET N° P5000 GB	REV 2
--------------	----------------------------------	--	----------

SCALE WITHOUT

DATE 13/07/16

SHEET 1 OF 1

THIS DOCUMENT MAY BE MODIFIED WITHOUT NOTICE